

| Model  | Net weight<br>(kg) | Depth<br>(mm) | Overall Ø<br>(mm) | Baffle<br>Cut-out Ø<br>(mm) | N° of<br>mounting holes | Voice coil Ø<br>(mm) |
|--------|--------------------|---------------|-------------------|-----------------------------|-------------------------|----------------------|
| B15EX  | 13.750             | 235           | 402               | 360                         | 8 at 45°<br>Ø 382mm     | 66                   |
| LB12EX | 9.650              | 190           | 314               | 283                         | 8 at 45°<br>Ø 296mm     | 45                   |
| LB12   | 6.250              | 140           | 314               | 283                         | 8 at 45°<br>Ø 296mm     | 45                   |
| LB8EX  | 5.5                | 165           | 210-235           | 187                         | 4 at 90°<br>Ø 217mm     | 38                   |
| LB8    | 2.875              | 96            | 210-235           | 187                         | 4 at 90°<br>Ø 217mm     | 38                   |
| LB7    | 2.450              | 87            | 174               | 146                         | 4 at 90°<br>Ø 161mm     | 38                   |
| LB6    | 1.350              | 72            | 136-151           | 116                         | 4 at 90°<br>Ø 139mm     | 25                   |
| LB5    | 1.250              | 64            | 110-126           | 94                          | 4 at 90°<br>Ø 114mm     | 25                   |
| MA5    | 1.250              | 64            | 110-126           | 94                          | 4 at 90°<br>Ø 114mm     | 25                   |